



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04N 7/52	A1	(11) International Publication Number: WO 99/52298 (43) International Publication Date: 14 October 1999 (14.10.99)
---	-----------	--

(21) International Application Number: PCT/GB99/01041

(22) International Filing Date: 6 April 1999 (06.04.99)

(30) Priority Data:
9807295.2 3 April 1998 (03.04.98) GB

(71) Applicant (for all designated States except US): SNELL & WILCOX LIMITED [GB/GB]; 6 Old Lodge Place, St. Margaret's, Twickenham, Middlesex TW1 1RQ (GB).


(72) Inventor; and
(75) Inventor/Applicant (for US only): FLANNAGHAN, Barry [GB/GB]; 45 Church Road, Steep, Hampshire GU32 2DN (GB).

(74) Agents: GARRATT, Peter, Douglas et al.; Mathys & Squire, 100 Gray's Inn Road, London WC1X 8AL (GB).

(81) Designated States: AU, CA, JP, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

Published
With international search report.

(54) Title: IMPROVEMENTS RELATING TO AUDIO-VIDEO DELAY



(57) Abstract

In digital video synchronisation, the trend in delay is monitored to enable a prediction to be made of the dropping or repeating of a video field. The audio time compression or expansion is then initiated a selected time interval in advance of the field the dropping or repeating. The loss of audio synchronisation can in this way be kept below perceptible thresholds.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Larvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

IMPROVEMENTS RELATING TO AUDIO-VIDEO DELAY

This invention relates to the processing of audio and video signals.

A common problem in the broadcast environment is the difference in delay experienced by the audio and video processes. With many new digital video processes in the signal chain and the consequential need for re-
5 synchronisation, the delay of the video may often differ significantly from that of the audio. This causes the well known lip-sync error problem.

A video synchroniser operates by re-timing and, where necessary, either dropping or inserting fields. Each video synchroniser may therefore add up to 40ms of video delay in a 50 field per second system such as PAL
10 or 34ms in NTSC or other 60Hz systems. The precise delay will depend on often arbitrary system clocks. In new installations the audio is often "embedded" in the video channel and so when passing through the synchroniser it will experience the same delay as the video.

Since a discontinuity of 40ms (or 34ms at 60Hz) is unacceptable in
15 audio, a temporary loss of lip sync is inevitable. In order to recover lip sync, the audio signal is time compressed or expanded for a period of time. This period of time must be sufficiently long that the resultant pitch change or other degradation remains imperceptible and will amount to several seconds. Over these several seconds, the loss of lip sync can be seriously objectionable.

20 It can be shown that a loss of synchronisation in which the audio arrives early, is particularly noticeable. It has been suggested that in the case of the audio being earlier than the video a delay much above 10ms is perceptible. In the opposite sense, with the audio being delayed, a delay of up to 30ms may be tolerated.

25 It is an object of the present invention to provide an improved method of managing differential delay of digital audio and video signals.

Accordingly, the present invention consists in one aspect in a digital video synchronisation process in which digital video and audio signals are delayed by the same varying amount to ensure synchronisation with a timing
30 reference and, on dropping or repeating of a video field, the audio signal is time compressed or expanded to recover audio/video synchronisation over a time period governed by the maximum acceptable pitch change or other

degradation, characterised in that the trend in delay is monitored to enable prediction of the dropping or repeating of a video field and in that said time compression or expansion is initiated a selected time interval in advance thereof.

5 In one form of the invention, this time interval is selected to minimise the perceived loss of audio/video synchronisation. That is to say, regard is had to the asymmetry in the thresholds for perceived loss of synchronisation for advanced and retarded audio.

The invention will now be described by way of example with reference
10 to the accompanying drawing which is a block diagram of a digital video synchroniser according to the invention.

The video synchroniser shown in the drawing receives a digital video input signal with embedded audio and provides as an output synchronised with an externally generated timing reference, a digital video signal, again
15 with embedded audio.

Digital video first passes into block 10; this extracts the audio data and the timing signals. Video passes to the main memory 12 to be delayed until it is co-timed with the output timing signal extracted by block 14 from the reference input. Block 16 measures the delay between the input and output
20 timing signals and passes this figure to a microprocessor 18. The calculated delay is passed to the audio data memory 20. The audio data and video data memories now give an identical delay. A re-sampling digital filter 22 alters the audio data sampling rate to match the outgoing video in order that the audio data can be synchronously inserted by block 24 into the outgoing video data
25 stream.

A synchroniser such as this, when its input and output timing references are of a different frequency, as is usual, will occasionally drop or repeat a video frame. In effect, it gains or loses 40ms (at 50Hz). Whereas the resulting picture disturbance is often imperceptible, the same is not true for
30 audio - it is not possible to cut or add 40ms of audio without major disturbance.

A typical implementation will compensate by re-sampling the audio to a higher or lower frequency. In the case where the video memory has lost a

frame, the microprocessor 18 will initiate a process of reading extra audio samples from the audio memory 20. A pitch change results, but if this is kept to less than 1%, it is unlikely to be noticed. Thus, after a synchroniser drops or repeats a frame the audio will initially be adrift by a noticeable 40ms. After
5 8 seconds (assuming 0.5% pitch change) the audio and video will once again be co-timed. As a result, there will be a perceptible error for up to 6 seconds.


In the improved system according to this invention, the microprocessor 18 will continually monitor the video delay and calculate the rate of change of delay over time. With the highly stable timing references that are generally in
10 use, it will usually be possible to predict accurately the time that the video memory will drop or gain a frame. Where it is predicted that, at the current rate of change, a video frame is due to be lost in 6 seconds time, the processor will initiate an increase in the audio delay to give a 0.5% pitch change. Just before the frame loss, the audio will be 30ms (at 50Hz) delayed
15 with respect to the video. If the above discussed thresholds for perception of an audio delay are correct, this loss in synchronisation is imperceptible. Immediately after the frame loss the audio will be 10ms early. If the above-discussed thresholds for perception of an audio advance are correct, this loss in synchronisation is similarly imperceptible. After a further 2 seconds, the
20 audio and video will be co-timed. Of course, the pitch change and the balance between worst case advance and delay may be controlled by the user. Use of the invention has in this example and on the assumed perception thresholds, replaced a synchronisation error which is perceptible for up to 6 seconds, by a synchronisation error which is not perceptible at all.

25 When it is predicted that, at the current rate of change, a video frame is due to be repeated in 2 seconds time the processor will initiate an decrease in the audio delay to give a 0.5% pitch change. Once again the error will be imperceptible.

It will be understood that the invention has been described by way of
30 examples only. Thus, rate conversion is only one example of a technique for time compression or expansion of the audio signal. Numerous alternative techniques, such as silence compression, will be known to the skilled reader and fall within the scope of the claimed invention.

CLAIMS

1. A digital video synchronisation process in which digital video and audio signals are delayed by the same varying amount to ensure synchronisation with a timing reference and, on dropping or repeating of a video field, the audio signal is time compressed or expanded to recover audio/video synchronisation over a time period governed by the maximum acceptable pitch change or other degradation, characterised in that the trend in delay is monitored to enable prediction of the dropping or repeating of a video field and in that said time compression or expansion is initiated a selected time interval in advance thereof.
2. A process according to Claim 1, wherein said time interval is selected to minimise the absolute loss of audio/video synchronisation.
3. A process according to Claim 1, wherein said time interval is selected to minimise the perceived loss of audio/video synchronisation.
4. A process according to Claim 3, wherein said time interval is selected such that the period for which the audio is delayed with respect to the video is greater than the period the period for which the audio is advanced with respect to the video.



INTERNATIONAL SEARCH REPORT

Inter. Appl. No.
PCT/GB 99/01041

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 H04N7/52

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H04N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 94 29979 A (INTELLIGENCE AT LARGE INC) 22 December 1994 (1994-12-22) abstract figure 13 page 6, line 1 - page 7, line 8 page 32, line 15 - line 26	1-4
A	KIRBY D G ET AL: "A NEW TECHNIQUE TO MAINTAIN SOUND AND PICTURE SYNCHRONISATION" EBU REVIEW- TECHNICAL, no. 264, 1 January 1995 (1995-01-01), pages 13-21, XP000670474 ISSN: 0251-0936 paragraph '0003! figures 2,3	1-4

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

22 July 1999

Date of mailing of the international search report

29/07/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Berbain, F

INTERNATIONAL SEARCH REPORT

Inter. Jnal Application No

PCT/GB 99/01041

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	"METHOD FOR SYNCHRONIZING AN AUDIO DIGITAL DATA STREAM WITH ANOTHER INFORMATION STREAM" IBM TECHNICAL DISCLOSURE BULLETIN, vol. 38, no. 4, 1 April 1995 (1995-04-01), page 141 XP000516100 ISSN: 0018-8689 the whole document	1-4
A	US 5 603 016 A (DAVIES ROBERT L) 11 February 1997 (1997-02-11) abstract column 1, line 66 - column 2, line 31	1-4
A	EP 0 648 056 A (THOMSON CONSUMER ELECTRONICS) 12 April 1995 (1995-04-12) abstract figure 2	1-4
A	KAWAHARA K ET AL: "A SINGLE CHIP MPEG1 DECODER" 1995 SYMPOSIUM ON VLSI CIRCUITS, KYOTO, JUNE 8 - 10, 1995, 8 June 1995 (1995-06-08), page 65/66 XP000557803 INSTITUTE OF ELECTRICAL AND ELECTRONICS ENGINEERS ISBN: 0-7803-2600-8 paragraph '04.2!	1-4

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 99/01041

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9429979	A	22-12-1994	AU 7206994 A CA 2173355 A EP 0739558 A NZ 268754 A US 5623490 A	03-01-1995 22-12-1994 30-10-1996 28-07-1998 22-04-1997
US 5603016	A	11-02-1997	NONE	
EP 0648056	A	12-04-1995	US 5430485 A AU 684520 B AU 7027894 A CA 2132186 A CN 1110854 A DE 69417139 D FI 944529 A JP 7177479 A PL 305189 A TR 28210 A US 5467139 A	04-07-1995 18-12-1997 13-04-1995 31-03-1995 25-10-1995 22-04-1999 31-03-1995 14-07-1995 03-04-1995 01-03-1996 14-11-1995